

Power packs

Power packs

Applications

- Used for easily providing power to hydraulic tools at any jobsite

Features

- Easy site-to-site transport with no need for towing
- Thermostatically controlled oil cooler for fast warm-up and help preventing the hydraulic oil from overheating
- Variable-flow on/off valve for simple tool changes and slow start-up
- Gauge displays when it's time to change the filter
- Available in Gasoline, diesel and electrically driven versions
- Several models equipped with Power
- On Demand, a system that saves fuel by automatically idling the engine when the tool isn't being used and speeding up when the tool is activated



Hydraulic Power Packs	PAC P9	PAC P13	PAC P18-30**	PAC P18+	PAC E6
Weight Including Oil kg (lb)	72 (159)	91.4 (202)	134 (295)	140 (308)	70 (154)
Length mm (in)	710 (28)	745 (29.3)	930 (36.6)	930 (36.6)	710 (28)
Width mm (in)	525 (20.7)	600 (23.6)	603 (23.7)	603 (23.7)	525 (20.7)
Height mm (in)	585 (23)	705 (27.8)	765 (30)	765 (30)	585 (23)
Oil Flow lpm (gpm)	20 (5)	20-30 (5-8)	20-30 (5-8)	2x15-20 (4-5) 1x30-40 (8-10.5)	20 (5)
Maximum Pressure bar (psi)	150 (2175)	150 (2175)	172 (2495)	145 (2103)	150 (2175)
Fuel Capacity L (gal)	6 (1.3)	6.5 (1.4)	8.5 (1.9)	8.5 (1.9)	–
EHTMA Class	C	C/D	C/D	B/C/D/E	C
Sound Power Level Guaranteed (2000/14/EC) dB(A)	101	101	101	101	96
Sound Pressure Level (ISO 11203) (Lp, r=1m) dB(A)	88	89	89	89	79
Power on Demand (POD)	Yes	Yes	No	No	No
Oil Control – Engine Oil	Yes	Yes	Yes	Yes	No
Electric Start	No	No	Yes	Yes	Yes
Engine Model kW (hp) or kW / V	Honda Gasoline 6.7 (9)	Honda Gasoline 9.7 (13)	B&S Vanguard Gasoline 13.4 (18)	B&S Vanguard Gasoline 13.4 (18)	5.5 kW / 3x400 V 16A Electric
Part Number	1807 0080 53*	1807 8000 06*	1807 8000 27	1807 8000 10	1807 0080 55

* PAC P18-30 will be available soon

NOTE: All values measured at 6 bar (87 psi) except sound data, which was measured at 6.2 bar (89 psi).