

# Generators

Tough Reliable Power

## Light Construction



EF2600

### FEATURES

- Meets CARB Emissions Regulations
- Voltmeter Provides Easy to Read Output Voltage
- Oil Watch Warning System Prevents Engine Damage in the Event of a Low Oil Situation
- Fuel Gauge
- Oversized Fuel Tank Offers a full work day of operation
- On a Single Tank of Fuel
- Full Roll Cage Protection
- Vibration Isolators
- Specialty Designed Muffler Reduces the Weight and the Noise

MODEL	Voltage	Max Amps	Surge Watts	Rated Watts	Engine Model	dBa Level	1/2 Load Run Time	Starting Method	Dry Weight
EF2600	120	21.6	2000	2300	MZ775	68	8.5 hours	Recoil	92.6 lbs
EF5500DE	120/240	44/23	5000	6500	MZ590	74.1	9 hours	Recoil Electric	234 lbs
EF7200DE	120/240	60/38	7500	9000	MZ590	74.5	8 hours	Recoil Electric	238 lbs

## Heavy Construction



EF7200DE

EF5500DE

### FEATURES

- Meets CARB and OSHA Emissions Regulations
- GFCI Recepticals
- Voltmeter Provides Easy to Read Output Voltage
- Oil Watch Warning System Prevents Engine Damage in the Event of a Low Oil Situation
- Fuel Gauge
- Lifting Eye
- Oversized Fuel Tank Offers a full work day of operation
- On a Single Tank of Fuel
- Wheel Kit and Battery Standard
- Full Roll Cage Protection
- Vibration Isolators
- Electric or Recoil Starting

- Wheel Kit and Battery Standard
- Full Roll Cage Protection
- Vibration Isolators
- Electric or Recoil Starting

# Inverters

Whisper Quiet  
Clean Power

Protects Sensitive Electronics

## Light Construction and Outdoor Activities



EF3000iS

EF2800i

EF2000iSV2

### FEATURES

- 12v DC Output and Harness
- GFCI Receptical (2800i)
- Vibration Isolators
- Oil Watch Warning System (2800i & 3000iS)
- Fuel Gauge
- Smart Throttle Reduces Engine RPM Based on Load Requirements
- Wheels Standard (3000iS)
- Full Roll Cage (2800i)
- 1/4 Load Run Times up to 18hrs

MODEL	Voltage	Max Amps	Surge Watts	Rated Watts	Surge Motor Model	dBa Level	1/4 Load Run Time	Starting Method	Dry Weight
EF2000iSV2	120	18.7	2000	1600	MZ510	61	10.5 hours	Recoil	44.1 lbs
EF2800i	120	23.3	2000	2500	MZ775	68	14.7 hours	Recoil	68 lbs
EF3000iS	120	30.0	3000	2800	MZ775	60	18.6 hours	Recoil	136 lbs
EF4500iSE	120	37.5	4500	4000	MZ590	60	15.2 hours	Electric	194 lbs
EF5000iDE	120/240	22.5/12.3	8000	5500	MZ590	64	13.3 hours	Electric	200 lbs

## Heavy Construction and Back up Power Supply



EF6300iSDE

EF4500iSE

### FEATURES

- CARB Compliant
- GFCI Recepticals (6300)
- Voltmeter Provides Easy to Read Output Voltage
- Oil Watch Warning System Prevents Engine Damage
- Fuel Gauge
- Dual Voltage 120/240 (6300)
- Wheels and Battery Standard
- Twin Bars Aids Transport and Security points
- Noise Block Quiet Enclosures for Pleasant Noise Quality.
- Electric Start
- Smart Throttle Reduces Engine RPM Based on Load Requirements
- 1/4 Load Run Times up to 16hrs